

The Sonus SBC 2000™ Session Border Controller

Communications devices are growing smaller and smarter, so Sonus designed a Session Border Controller (SBC) that was smaller and smarter, too. The SBC 2000 Session Border Controller is an advanced SBC independently verified for performance, delivering robust security features and interoperability between disparate networks. The SBC 2000 configurations are designed for ease of deployment and growth. Both session and port expansion can be remotely enabled via a simple license, eliminating the need for a truck-roll and an on-site technician. The Sonus SBC 2000 also features a wide range of I/O and call capacities as well as built-in survivability for Microsoft® Skype® for Business, BroadSoft™, and other SIP/TDM/FXx clients, so calls go through even if the wide area network (WAN) goes down.

System Capabilities

- Sessions
 - Maximum number of total concurrent calls: 600
 - Maximum number of TDM-to-SIP calls: 480
 - Maximum number of SIP-to-SIP calls: 600
 - Maximum number of transcoded sessions (based upon codec type): 600
 - Maximum number of total concurrent calls associated with Survivable Branch Appliance (SBA): 240
- Call Set-Up
 - Maximum call set-up rate: 4 cps
- Registrations
 - Maximum number of registered users: 1,000
- Encryption
 - Maximum number of TLS sessions: 600
 - Maximum number of SRTP sessions: 600
- Business Continuity
 - PSTN fallback when WAN is down
 - Site survivability for SIP clients through built-in SIP registrar
 - Survivable Branch Appliance (SBA) for Skype for Business and Lync®
 - Resilient Branch Appliance (RBA) for Lync survivability over 3G/4G
 - Local survivability with BroadWorks
 - Multiple SIP trunking service provider support for redundancy
 - ITSP E911 Support
 - Redundant Ethernet ports and multiple spanning trees

Management Capabilities

- Operations, Administration and Management
 - Single, secure, web-based GUI with real-time monitoring
 - REST-based programmatic interface to remotely manage multiple SBC 2000s



The Sonus SBC 2000

- SNMP v2c for comprehensive network management using third-party management systems
- Configuration backup and restore; Configuration upload from one site to another; Partial configuration import/export through REST
- CDR Reporting
- Syslogs and local logging for troubleshooting, with support for free Sonus LX syslog server and log parser tool
- Historical Stats and TCAs
- Authentication
 - Local user (User name/password)
 - Active Directory®
 - RADIUS

Media Services

- G.711, G.722, G.722.2 (AMR-WB), G.723.1, G.726 (32 kbps), G.729A/B (8 kbps), T.38
- Transcoding
- Video
- T.38 with CNG tone detection
- DTMF/RFC4733; Inband DTMF; SIP INFO/RFC-2833
- Voice Activity Detection (VAD)
- G.168 Echo Cancellation with standard 128 ms tail length
- Comfort noise generation and packet loss concealment
- Automatic call type detection – voice, fax or modem
- Music on-hold
- Generate call progress tones – ringback, busy, re-order
- RTP inactivity monitoring (dead call detection)
- RTP pass-through and media bypass
- RTCP/RTCP-XR
- Caller ID support

Signaling

- Maximum number of signaling groups: 100
- TDM Signaling (ISDN): AT&T 4ESS/5ESS, Nortel DMS-100, Euro ISDN (ETSI 300-102), QSIG, NTT InsNet (Japan), ANSI National ISDN-2 (NI-2)
- TDM Signaling (CAS): T1 CAS (E&M, Loop start); E1 CAS (R2)
- Back-to-Back User Agent (B2BUA)
- SIP (UDP/TCP/TLS) to/from SIP (UDP/TCP/TLS)
- SIP (UDP/TCP/TLS) to/from CAS/PRI/FXS
- CAS/PRI/FXS to/from CAS/PRI/FXS
- SIP Message Manipulation (SMM)

Protocol Support

- SNMPv2c
- NTP
- HTTPS
- RIPv2, OSPF as dynamic IP routing protocols
- RTP/RTCP, SRTP/SRTCP
- SIP over UDP, TCP, TLS
- IPv4, IPv6, and IPv4/IPv6 interworking
- DNS
- DHCP server
- DHCP client
- Asynchronous DNS for SIP
- NAT
- Support for Reason Header

Routing/Policy

- Maximum number of call route entries: 15,000
- Active Directory/LDAP-based call routing
- Routing based on quality metrics
- Least cost routing
 - Event-based action set
- On-board call forking (up to eight end points)
- Supplementary services
 - Call hold
 - Call transfer (blind & assisted)
 - Call forward
- Embedded policy/routing engine
- Optional centralized policy/routing via Sonus Centralized Policy Server (PSX Server) using SIP
- Screening, blocking, routing, presentation, call type filters
- Route prioritization
- Leading digit routing; International routing; URI-based routing
- Digit manipulation (name/number manipulation using regular expression and Active Directory lookup)
- SIP routing
 - Based on source and destination IP address
 - Fully Qualified Domain Name (FQDN)
- Detect proxy failure and route to alternate paths
- Re-route on failure based on full Cause Code re-routing on T1/E1 trunks

- Lync E911 support; SIP/PIDF-LO passthrough and ELIN Gateway
- One number fax support (single DID for voice and fax)

Security

- TLS for signaling encryption
- Secure RTP (SRTP) for media encryption
- Built-in VoIP firewall
- Microsoft Windows® firewall for Application Solution Module to manage Lync SBA
- Topology hiding; User privacy
- Prevention of Denial-of-Service (DoS) and Distributed DoS (DDoS) attacks
- Dialed Number Identification Service (DNIS), Calling Line Identification (CLID), Call type pre-authentication
- Traffic separation (VLAN interface separation)
- Malformed packet protection
- Access Control Lists (ACLs)
- IPsec VPN tunnel
- NAT/NAPT and port forwarding, NAT traversal
- Duplicate IP detection on ASM/SBA

Quality of Service (QoS)

- Bandwidth management
- Call Admission Control (CAC) (deny excessive calls based on static configuration for bandwidth management)
- P-time mediation for rate limiting
- Per-call statistics
- Diffserv/DSCP marking

Packet Network Time Source

- Network Time Protocol (NTP) per RFC1708

Microsoft Skype for Business Support

- Qualified as a Survivable Branch Appliance (SBA) for Microsoft Lync 2010, Lync 2013, and Skype for Business deployments
- Qualified as an Enhanced Gateway for Lync 2013, Lync 2010 & Skype for Business deployments
- Lync 2013 and Lync 2010 qualified for SBC and E-911 ELIN Gateway
- Microsoft Office 365® Exchange Unified Messaging qualified
- Non-Lync SIP client user state reporting (e.g., presence, user busy, etc.) to Lync clients
- Microsoft SCOM support

- Lync Quality of Experience (QoE) monitoring collects call RTP stream data and sends to Lync QoE server
 - Round Trip Delay
 - Jitter (max, mean)
 - Packet Loss (max, mean)
 - Packet Loss Rate (max, mean)
 - Burst (density, gap density)
 - MOS-LQ, MOS-CQ
 - Signal/Noise Level
 - Microsoft Systems Center 2012 R2
- Skype for Business SDN API 2.2 support
- Integration with PeterConnects® Attendant, Directory, and Manager/Assistant (for SBA clients)
- Integration with Nectar Unified Communications Management Platform (UCMP)
- Integration with Event Zero UC Commander™ (for SBA clients)

Server Module

Memory

- 8 GB of DDR4 with ECC (Error-Correcting Code)

CPU

- Intel® Pentium® Processor: Broadwell family, dual core, 4 threads, 2.20 GHz

Storage

- 256 GB SSD

Capabilities

- Maximum number of Microsoft Skype for Business/Lync users associated with the Survivable Branch Appliance: 1000
- Maximum number of concurrent calls associated with Microsoft Skype for Business/Lync Survivable Branch Appliance: 240
- Validated as interoperable with BroadWorks Release 19.sp1 and compatible with BroadWorks Releases 18.0, 18.sp1, 19.0 SIP interface
- 2 Microsoft Hyper-V® enabled VOSEs (Virtual Operating System Environments) to support hosting of 3rd party applications (Windows Server 2012 R2 only)

Operating System

- Microsoft Windows Server® 2012 R2, Windows Server 2008 R2

Redundancy

- Redundant power supply

Additional Hardware Specifications

Front Panel

- Status indicators front panel LEDs
 - Power
 - Alarm
 - Peer node
 - Ready
- Dual USB 2.0 interface for main SBC board
- Additional dual USB 2.0 ports for ASM (optional)
- WAN and LAN Interfaces
 - 4 x 10/100/1000 BASE-T Ethernet ports with VLAN support
 - Auto-MDIX
- Administration Port
 - 1 x 10/100/1000 BASE-T Ethernet port

Rear Panel

- Physical PSTN Interfaces
 - Up to 16 T1/E1 - 2 x from one to eight T1/E1 spans per digital module
 - Up to 48 FXS ports - 2 x 24 ports

Chassis

- 1U, rack mount
- Inches: 17.5" wide x 1.75" high x 21" deep
- Centimeters: 44.4 wide x 4.4 high x 53.4 deep

Chassis Mounting Options

- EIA-standard 19" equipment rack with 2 or 4 posts (for 4-post racks: mounting equipment is provided with a depth of 24" or 30")

AC Power Option

- Input Voltage: 100-240 VAC nominal, auto-switching, 47-63 Hz
- AC Maximum Input Current: 3.0A at 115 VAC; 1.6A at 230 VAC
- AC Input Voltage Range (Nominal): 100-127 VAC and 200-240 VAC
- Max Power Consumption: 360 W

Cooling System

- Internal forced convection

Weight Maximum Fully Populated

- 23 lbs. (10.43 kg)

Environmental

- 5 to 40° C operating
- -40 to 70° C storage
- 5 to 85% non-condensing operating humidity

About Sonus Networks

Sonus enables and secures real-time communications so the world's leading service providers and enterprises can embrace the next generation of SIP and 4G/LTE solutions, including VoIP, video, instant messaging, and online collaboration. With customers in more than 50 countries and nearly two decades of experience, Sonus offers a complete portfolio of hardware-based and virtualized Session Border Controllers (SBCs), Diameter Signaling Controllers (DSCs), Cloud Exchange Networking Platform, policy/routing servers, and media and signaling gateways. For more information, visit www.sonus.net or call 1-855-GO-SONUS. Sonus is a registered trademark of Sonus Networks, Inc. All other company and product names may be trademarks of the respective companies with which they are associated.

Sonus Networks North American Headquarters

4 Technology Park Drive
Westford, MA 01886
U.S.A.
Tel: +1-855-GO-SONUS

Sonus Networks APAC Headquarters

1 Fullerton Road #02-01
One Fullerton
Singapore 049213
Singapore
Tel: +65-68325589

Sonus Networks EMEA Headquarters

Edison House
Edison Road
Dorcan, Swindon
Wiltshire
SN3 5JX
Tel: +44-14-0378-8114

Sonus Networks CALA Headquarters

Homero No. 1933-902
Col. Los Morales, C.P. 11510
Mexico City, Mexico
Distrito Federal
Mexico Tel: +52-55-1950-3036
Int'l Tel: +1-978-614-8741

To learn more, call Sonus at 855-GO-SONUS
or visit us online at www.sonus.net

Microsoft Partner
Gold Communications

Voice
Unified Communications
Business Productivity Solutions
Midmarket Solution Provider

The content in this document is for informational purposes only and is subject to change by Sonus Networks without notice. While reasonable efforts have been made in the preparation of this publication to assure its accuracy, Sonus Networks assumes no liability resulting from technical or editorial errors or omissions, or for any damages resulting from the use of this information. Unless specifically included in a written agreement with Sonus Networks, Sonus Networks has no obligation to develop or deliver any future release or upgrade, or any feature, enhancement, or function.

Copyright © 2016 Sonus Networks, Inc. All rights reserved. Sonus is a registered trademark of Sonus Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks may be the property of their respective owners.