

The Sonus SBC SWe Lite™ Session Border Controller

The Sonus Session Border Controller Software Edition Lite (SBC SWe Lite) is an SBC optimized for small and mid-sized business (SMB) virtualized networking environments. The SBC SWe Lite delivers virtualized Customer Premises Equipment (vCPE) interworking, security and survivability for Unified Communications (UC) or SIP trunking. With support for popular virtualization environments such as Microsoft® Hyper-V®, VMware® vSphere® Hypervisor and Linux™ KVM, the SBC SWe Lite can be installed quickly and easily.



The Sonus SBC SWe Lite derives its feature set from a common code base with the Tolly® certified and Miercom® performance verified SBC 1000 SBC 1000 and SBC 2000 products. As such, customers can expect the same advantages when transitioning to UC or SIP trunking – an SBC that protects your voice infrastructure from Denial of Service (DoS)/Distributed DOS (DDOS) attacks, maintains privacy, encrypts your calls, and interworks with a wide variety of third-party SIP and legacy voice infrastructure devices/services, all while providing reliable, scalable performance that ensures maximum uptime and service availability.

By offering the same management and provisioning interface as the Sonus SBC 1000/SBC 2000, the SBC SWe Lite dramatically speeds configuration through the simple and highly intuitive configuration wizard. In addition, the common code base affords the SBC SWe Lite a benefit unmatched by many competitors: an extremely compact CPU, RAM and program/data store footprint uniquely positioned for highly constrained vCPE processing environments. The result is clear: customers significantly reduce the costs and complexities of deploying vCPE devices in support of UC/SIP trunking.

Single Instance Capabilities

- Maximum number of SIP ↔ SIP sessions: 100
- Maximum number of RTP ↔ RTP sessions (direct media or RTP proxy mode): 100
- Maximum number of transcode sessions (G.711 ↔ G.729): 25
- Call Setup
 - Maximum call setup rate: 10 cps
- Registrations
 - Maximum number of registered users: 1,000
- Encryption
 - Maximum number of TLS-encrypted SIP sessions: 100
 - Maximum number of RTP ↔ SRTP sessions: 25
 - Maximum number of SRTP ↔ SRTP sessions (direct media or RTP proxy mode): 100
- Business continuity
 - Site survivability for SIP clients through built-in SIP registrar
 - Local survivability with BroadWorks
 - Multiple SIP trunking service provider support for redundancy
 - ITSP E911 Support

Management Capabilities

- Operations, administration and management
 - Single, secure, web-based GUI with real-time monitoring
 - REST-based programmatic interface to remotely manage multiple SBC SWe Lites
 - SNMPv2c for comprehensive network management using third-party management systems
 - Configuration backup and restore; configuration upload from one site to another; partial configuration import/export through REST
 - CDR reporting
 - Syslog for troubleshooting, with support for complimentary Sonus LX syslog server and log parser tool
 - Historical stats and TCAs

- Authentication
 - Local user (User name/password)
 - Active Directory®
 - RADIUS

Media Services

- Supported codecs (including for transcode operations): G.711, G.722, G.722.2 (AMR-WB), G.723.1 (5.3 kbps, 6.3 kbps), G.726 (32 kbps), G.729A/B (8 kbps)
- DTMF/RFC4733; Inband DTMF; SIP INFO/RFC-2833
- Voice Activity Detection (VAD)
- G.168 Echo Cancellation with standard 128 ms tail length
- Comfort noise generation and packet loss concealment
- Automatic call type detection – voice, fax or modem
- Music on hold
- Generate call progress tones – ring back, busy, re-order
- RTP inactivity monitoring (dead call detection)
- RTP pass-through and media bypass
- RTCP
- Caller ID support

Signaling

- Maximum number of signaling groups: 100
- Back-to-Back User Agent (B2BUA)
- SIP (UDP/TCP/TLS) to/from SIP (UDP/TCP/TLS)
- SIP Message Manipulation (SMM)

Protocol Support

- SNMPv2c
- NTP
- HTTPS
- RTP/RTCP, SRTP/SRTCP
- SIP over UDP, TCP, TLS
- DNS
- RIPv2, OSPF as dynamic IP routing protocols
- DHCP client
- Asynchronous DNS for SIP
- NAT
- IPv4
- Support for Reason Header interworking

Routing/Policy

- Maximum number of call route entries: 1,000
- Active Directory/LDAP-based call routing
- Routing based on quality metrics
- Least-cost routing
 - Event-based action set
- On-board call forking (up to eight end points)
- Supplementary services
 - Call hold
 - Call transfer (blind & assisted)
 - Call forward
- Embedded policy/routing engine
- Optional centralized policy/routing via Sonus Centralized Policy Server (PSX Server) using SIP
- Screening, blocking, routing, presentation, call type filters
- Route prioritization
- Leading digit routing; international routing; URI-based routing
- Digit manipulation (name/number manipulation using regular expression and Active Directory lookup)
- One-number fax support (single DID for voice and fax)
- SIP routing
 - Based on source and destination IP address
 - Fully Qualified Domain Name (FQDN)
- Detect proxy failure and route to alternate paths
- Re-route on failure based on based on cause code
- Lync E911 support; SIP/PIDF-LO pass-through

Security

- TLS 1.2 for signaling encryption
- Secure RTP (SRTP) for media encryption
- Built-in VoIP firewall
- Topology hiding; User privacy
- Prevention of Denial-of-Service (DoS) and Distributed DoS (DDoS) attacks
- Dialed Number Identification Service (DNIS), Calling Line Identification (CLID), Call type pre-authentication
- Malformed packet protection
- Access Control Lists (ACLs)
- NAT/NAPT and port forwarding, NAT traversal

Quality of Service (QoS)

- Bandwidth management
- Call Admission Control (CAC) (deny excessive calls based on static configuration for bandwidth management)
- P-time mediation for rate limiting
- Per-call statistics
- DiffServ/DSCP marking

Packet Network Time Source

- Network Time Protocol (NTP) per RFC 1708

Microsoft® Skype® for Business Support

- Certified as an SBC for Skype for Business deployments
- Lync Server 2013 and Lync Server 2010 qualified for SBC
- Qualified for Microsoft Office 365® Exchange Unified Messaging
- Non-Lync SIP client user state reporting (e.g., presence, user busy, etc.) to Lync clients
- Microsoft SCOM support

Virtual Machine System Requirements

CPU

- 1 virtual CPU (vCPU); processing recommended on a second generation Intel® Core™ or Intel® Xeon® processor

Memory

- 1 GB RAM

Hard Disk Drive (HDD)

- 5 GB

Virtual Network Interface Cards (vNICs)

- 5

Supported Virtual Machine Environments

- Microsoft® Hyper-V®
- VMware® vSphere® Hypervisor (ESXi) Version 5.5 or above
- Linux™ KVM (Kernel-based Virtual Machine)

About Sonus Networks

Sonus enables and secures real-time communications so the world's leading service providers and enterprises can embrace the next generation of SIP and 4G/LTE solutions, including VoIP, video, instant messaging, and online collaboration. With customers in more than 50 countries and nearly two decades of experience, Sonus offers a complete portfolio of hardware-based and virtualized Session Border Controllers (SBCs), Diameter Signaling Controllers (DSCs), Cloud Exchange Networking Platform, policy/routing servers, and media and signaling gateways. For more information, visit www.sonus.net or call 1-855-GO-SONUS. Sonus is a registered trademark of Sonus Networks, Inc. All other company and product names may be trademarks of the respective companies with which they are associated.

Sonus Networks North American Headquarters

4 Technology Park Drive
Westford, MA 01886
U.S.A.
Tel: +1-855-GO-SONUS

Sonus Networks APAC Headquarters

1 Fullerton Road #02-01
One Fullerton
Singapore 049213
Singapore
Tel: +65-68325589

Sonus Networks EMEA Headquarters

Edison House
Edison Road
Dorcan, Swindon
Wiltshire
SN3 5JX
Tel: +44-14-0378-8114

Sonus Networks CALA Headquarters

Homero No. 1933-902
Col. Los Morales, C.P. 11510
Mexico City, Mexico
Distrito Federal
Mexico Tel: +52-55-1950-3036
Int'l Tel: +1-978-614-8741

To learn more, call Sonus at 855-GO-SONUS
or visit us online at www.sonus.net

Microsoft Partner
Gold Communications

Voice
Unified Communications
Business Productivity Solutions
Midmarket Solution Provider

The content in this document is for informational purposes only and is subject to change by Sonus Networks without notice. While reasonable efforts have been made in the preparation of this publication to assure its accuracy, Sonus Networks assumes no liability resulting from technical or editorial errors or omissions, or for any damages resulting from the use of this information. Unless specifically included in a written agreement with Sonus Networks, Sonus Networks has no obligation to develop or deliver any future release or upgrade, or any feature, enhancement, or function.

Copyright © 2017 Sonus Networks, Inc. All rights reserved. Sonus is a registered trademark of Sonus Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks may be the property of their respective owners.